

PRODUCT SPECIFICATION

176 Diameter Tripletite Cans



CAN SPECS

Can Details		2 Litre	4 Litre	5 Litre	6 Litre*
Ullage % (approx)		12	10	10	8
Height (mm)		100	192	237	278
Handle		NA	Standard	Standard	Standard
Packing Qty					
Bulk	No. per Layer	36	36	36	42
	No. per Pallet	252	216	180	168
Cartons	No. per Carton	36	18	6	NA
	No. of Cartons	12	12	36	NA
	No. per Pallet	432	216	216	NA
Height Tolerance		±1mm			
Handle		2.5 or 3.2mm wire			
Options					
Dangerous Goods Status		Not Approved for the Transportation of Dangerous Goods unless Limited Quantities Exceptions apply under ADGC 7th Edition Part 3 * 6 Litre is not Dangerous Goods approved			
Lid		176 TT			
Print Area		Request artwork template from Account Manager			



CAN COATINGS

Outside	Plain	(POS)
	White	(WOS)
	Varnish	(VOS)
Inside	Plain	(PIS)
	Lacquer	(LIS)

Issue Date: 15 July 2015

www.ncipackaging.com

Sales & Enquiries:

AUSTRALIA
1800 289 624

metal.enquiries@ncipackaging.com
90-92 Chifley Drive, Preston, VIC 3072

NEW ZEALAND
0800 220 120

windsor.yang@ncipackaging.com
80 Mt Wellington Hwy Panmure Auckland

PRODUCT SPECIFICATION

176 Diameter Tripletite Lids



LID SPECS

Diameter (mm)	169.9	
Height (mm)	9.5	
Packing Qty		
Carton	No. per Carton	224
	No. of Cartons	16
	No. per Pallet	3,584
Height Tolerance	±1mm	
Options		
Cans	To suit all 176 TT cans	
Print Area	Request artwork template from Account Manager	



LID COATINGS

Outside	Plain	(POS)
	White	(WOS)
	Varnish	(VOS)
Inside	Plain	(PIS)
	Lacquer	(LIS)

Issue Date: 15 July 2015

www.ncipackaging.com

Sales & Enquiries:

AUSTRALIA
1800 289 624

metal.enquiries@ncipackaging.com
90-92 Chifley Drive, Preston, VIC 3072

NEW ZEALAND
0800 220 120

windsor.yang@ncipackaging.com
80 Mt Wellington Hwy Panmure Auckland

NCI Packaging

PRODUCT SPECIFICATION

Appendix

COATINGS AND USES

Tinplate is steel sheet electroplated with tin to provide enhanced appearance and protection against rust. Coatings can be added to tinplate to enhance appearance and performance. Coatings and their typical uses* are listed below.

Outside	Plain	(POS) Use in dry environments where the risk of oxidation is low
	White	(WOS) Additional protection against oxidation of the container due to moisture Also used on most printed cans as the white base coating under colour print
	Varnish	(VOS) Clear finish for extra protection against oxidation of the container due to moisture
Inside	Plain	(PIS) Typical uses: Solvent based products Oil paints Edible oils Not suitable for: Water based products Olive oil
	Lacquer	(LIS) Typical uses: Water based products Water based paints Olive oil

* Uses above are suggestions only, customers are responsible for testing to ensure compatibility of containers with their packed product.

www.ncipackaging.com

Sales & Enquiries:

AUSTRALIA
1800 289 624

metal.enquiries@ncipackaging.com
90-92 Chifley Drive, Preston, VIC 3072

NEW ZEALAND
0800 220 120

windsor.yang@ncipackaging.com
80 Mt Wellington Hwy Panmure Auckland