

# PRODUCT SPECIFICATION

## 224 Diameter Tripletite Cans (DG)



### CAN SPECS

| Can Details            |                | 6 Litre                                                                  | 10 Litre |
|------------------------|----------------|--------------------------------------------------------------------------|----------|
| Ullage % (approx)      |                | 13                                                                       | 10       |
| Height (mm)            |                | 184                                                                      | 289      |
| Handle                 |                | Standard                                                                 | Standard |
| Packing Qty            |                |                                                                          |          |
| Bulk                   | No. per Layer  | 24                                                                       | 24       |
|                        | No. per Pallet | 144                                                                      | 96       |
| Cartons                | No. per Carton | NA                                                                       | NA       |
| Height Tolerance       |                | ±1mm                                                                     |          |
| Handle                 |                | 3.2mm wire plus optional plastic grip                                    |          |
| Options                |                |                                                                          |          |
| Dangerous Goods Status |                | When used with LokSafe™ PLUS plastic ring<br>Packing Group III / 1.2 max |          |
| Lid                    |                | 224 TT LokSafe™                                                          |          |
| Print Area             |                | Request artwork template from Account Manager                            |          |



### CAN COATINGS

|         |         |       |
|---------|---------|-------|
| Outside | Plain   | (POS) |
|         | White   | (WOS) |
|         | Varnish | (VOS) |
| Inside  | Plain   | (PIS) |
|         | Lacquer | (LIS) |

Issue Date: 15 July 2015

[www.ncipackaging.com](http://www.ncipackaging.com)

Sales & Enquiries:

**AUSTRALIA**  
**1800 289 624**

metal.enquiries@ncipackaging.com  
90-92 Chifley Drive, Preston, VIC 3072

**NEW ZEALAND**  
**0800 220 120**

windsor.yang@ncipackaging.com  
80 Mt Wellington Hwy Panmure Auckland

# PRODUCT SPECIFICATION

## 224 Diameter Tripletite Cans (non DG)



### CAN SPECS

| Can Details            |                | 6 Litre                                                | 10 Litre |
|------------------------|----------------|--------------------------------------------------------|----------|
| Ullage % (approx)      |                | 13                                                     | 10       |
| Height (mm)            |                | 184                                                    | 289      |
| Handle                 |                | Standard                                               | Standard |
| Packing Qty            |                |                                                        |          |
| Bulk                   | No. per Layer  | 24                                                     | 24       |
|                        | No. per Pallet | 144                                                    | 96       |
| Cartons                | No. per Carton | NA                                                     | NA       |
| Height Tolerance       |                | ±1mm                                                   |          |
| Handle                 |                | 3.2mm wire plus optional plastic grip                  |          |
| Options                |                |                                                        |          |
| Dangerous Goods Status |                | Not Approved for the Transportation of Dangerous Goods |          |
| Lid                    |                | 224 TT LokSafe™                                        |          |
| Print Area             |                | Request artwork template from Account Manager          |          |



### CAN COATINGS

|         |         |       |
|---------|---------|-------|
| Outside | Plain   | (POS) |
|         | White   | (WOS) |
|         | Varnish | (VOS) |
| Inside  | Plain   | (PIS) |
|         | Lacquer | (LIS) |

Issue Date: 15 July 2015

[www.ncipackaging.com](http://www.ncipackaging.com)

Sales & Enquiries:

**AUSTRALIA**  
**1800 289 624**

metal.enquiries@ncipackaging.com  
90-92 Chifley Drive, Preston, VIC 3072

**NEW ZEALAND**  
**0800 220 120**

windsor.yang@ncipackaging.com  
80 Mt Wellington Hwy Panmure Auckland

# PRODUCT SPECIFICATION

## 224 Diameter LokSafe™ Lids



### LID SPECS

|                  |                | LokSafe™                                                                        | LokSafe™ PLUS<br>(plastic DG ring) |
|------------------|----------------|---------------------------------------------------------------------------------|------------------------------------|
| Diameter (mm)    |                | 220.5                                                                           | 232.0                              |
| Height (mm)      |                | 11.2                                                                            | 17.8                               |
| Packing Qty      |                |                                                                                 |                                    |
| Carton           | No. per Carton | 100                                                                             | 105                                |
|                  | No. of Cartons | 16                                                                              | 16                                 |
|                  | No. per Pallet | 1,600                                                                           | 1,680                              |
| Height Tolerance |                | ±1mm                                                                            |                                    |
| Options          |                | LokSafe™ PLUS plastic ring for<br>DG applications (Packing Group III / 1.2 max) |                                    |
| Cans             |                | To suit all 224 TT cans                                                         |                                    |
| Print Area       |                | Request artwork template from Account Manager                                   |                                    |

### LID COATINGS

|         |         |       |
|---------|---------|-------|
| Outside | White   | (WOS) |
|         | Varnish | (VOS) |
| Inside  | Plain   | (PIS) |
|         | Lacquer | (LIS) |

Issue Date: 15 July 2015

[www.ncipackaging.com](http://www.ncipackaging.com)

Sales & Enquiries:

**AUSTRALIA**  
**1800 289 624**

metal.enquiries@ncipackaging.com  
90-92 Chifley Drive, Preston, VIC 3072

**NEW ZEALAND**  
**0800 220 120**

windsor.yang@ncipackaging.com  
80 Mt Wellington Hwy Panmure Auckland

# NCI Packaging

# PRODUCT SPECIFICATION

## Appendix

### COATINGS AND USES

Tinplate is steel sheet electroplated with tin to provide enhanced appearance and protection against rust. Coatings can be added to tinplate to enhance appearance and performance. Coatings and their typical uses\* are listed below.

|         |         |                                                                                                                                                                  |
|---------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Outside | Plain   | (POS)<br>Use in dry environments where the risk of oxidation is low                                                                                              |
|         | White   | (WOS)<br>Additional protection against oxidation of the container due to moisture<br>Also used on most printed cans as the white base coating under colour print |
|         | Varnish | (VOS)<br>Clear finish for extra protection against oxidation of the container due to moisture                                                                    |
| Inside  | Plain   | (PIS)<br><b>Typical uses:</b><br>Solvent based products<br>Oil paints<br>Edible oils<br><br><b>Not suitable for:</b><br>Water based products<br>Olive oil        |
|         | Lacquer | (LIS)<br><b>Typical uses:</b><br>Water based products<br>Water based paints<br>Olive oil                                                                         |

*\* Uses above are suggestions only, customers are responsible for testing to ensure compatibility of containers with their packed product.*

[www.ncipackaging.com](http://www.ncipackaging.com)

Sales & Enquiries:

**AUSTRALIA**  
**1800 289 624**

metal.enquiries@ncipackaging.com  
90-92 Chifley Drive, Preston, VIC 3072

**NEW ZEALAND**  
**0800 220 120**

windsor.yang@ncipackaging.com  
80 Mt Wellington Hwy Panmure Auckland