

PRODUCT SPECIFICATION

226 Diameter Tapered Pails



PAIL SPECS

Pail Details		10 Litre
Ullage % (approx)		8
Height (mm)		273
Handle		Standard
Packing Qty		
Bulk	No. per Layer	16
	No. per Pallet	230
Cartons	No. per Carton	NA
Height Tolerance	±1.5mm	
Handle	4.0mm wire plus optional plastic grip	
Options	Plastic grip	
Dangerous Goods Status	Packing Group II / 1.2 max when used with Polyseal lid and locking ring	
Lid	240 Polyseal or 240 Natseal and locking ring	
Print Area	Request artwork template from Account Manager	



PAIL COATINGS

Outside	Plain	(POS)
	White	(WOS)
	Varnish	(VOS)
Inside	Plain	(PIS)
	Lacquer	(LIS)

Issue Date: 15 July 2015

www.ncipackaging.com

Sales & Enquiries:

AUSTRALIA
1800 289 624

metal.enquiries@ncipackaging.com
90-92 Chifley Drive, Preston, VIC 3072

NEW ZEALAND
0800 220 120

windsor.yang@ncipackaging.com
80 Mt Wellington Hwy Panmure Auckland

PRODUCT SPECIFICATION

240 Lids for 226 Diameter Pails



LID SPECS

	240 Natseal	240 Polyseal (DG)
Diameter (mm)	252.8	252.8
Height (mm)	13.0	13.0
Packing Qty		
Carton	No. per Carton	40
	No. of Cartons	48
	No. per Pallet	1,920
Height Tolerance	±1.5mm	
Options	Use with 240 Locking Ring	
Pails	To suit all 226 pails	
Print Area	Request artwork template from Account Manager	

LID COATINGS

Outside	Plain	(POS)
	White	(WOS)
	Varnish	(VOS)
Inside	Plain	(PIS)
	Lacquer	(LIS)

Issue Date: 15 July 2015

www.ncipackaging.com

Sales & Enquiries:

AUSTRALIA
1800 289 624

metal.enquiries@ncipackaging.com
90-92 Chifley Drive, Preston, VIC 3072

NEW ZEALAND
0800 220 120

windsor.yang@ncipackaging.com
80 Mt Wellington Hwy Panmure Auckland

NCI Packaging

PRODUCT SPECIFICATION

Appendix

COATINGS AND USES

Tinplate is steel sheet electroplated with tin to provide enhanced appearance and protection against rust. Coatings can be added to tinplate to enhance appearance and performance. Coatings and their typical uses* are listed below.

Outside	Plain	(POS) Use in dry environments where the risk of oxidation is low
	White	(WOS) Additional protection against oxidation of the container due to moisture Also used on most printed cans as the white base coating under colour print
	Varnish	(VOS) Clear finish for extra protection against oxidation of the container due to moisture
Inside	Plain	(PIS) Typical uses: Solvent based products Oil paints Edible oils Not suitable for: Water based products Olive oil
	Lacquer	(LIS) Typical uses: Water based products Water based paints Olive oil

* Uses above are suggestions only, customers are responsible for testing to ensure compatibility of containers with their packed product.

www.ncipackaging.com

Sales & Enquiries:

AUSTRALIA
1800 289 624

metal.enquiries@ncipackaging.com
90-92 Chifley Drive, Preston, VIC 3072

NEW ZEALAND
0800 220 120

windsor.yang@ncipackaging.com
80 Mt Wellington Hwy Panmure Auckland