# **PRODUCT SPECIFICATION**

276 Diameter Pails (DG)





#### **PAIL SPECS**

Pail Details		10 Litre	15 Litre	20 Litre	21 Litre
	Ullage % (approx)	10	7	3	3*
	Height (mm)	205	286	357	377
Handle		Standard	Standard	Standard	Standard
Dangerous Goods Status		Packing Group II / 1.4 max	Packing Group II / 1.4 max	Packing Group II / 1.2 max	Packing Group II / 1.2 max
Packing Qty					
Bulk	No. per Layer	16	16	16	16
	No. per Pallet	160	160	144	144
Cartons	No. per Carton	NA	NA	NA	NA
Height Tolerance		±1.5mm			
Handle	4.0mm wire with plastic grip				
Options					
Lid	305 Polyseal and locking ring				
Print Area		Request artwork template from Account Manager			

<sup>\* 8%</sup> when used as 20 Litre



### **PAIL COATINGS**

Outside	Plain	(POS)
	White	(WOS)
	Varnish	(VOS)
Inside	Plain	(PIS)
	Lacquer	(LIS)

Issue Date: 23 April 2021

www.ncipackaging.com

Sales & Enquiries:

AUSTRALIA 1800 289 624 metal.enquiries@ncipackaing.com 90-92 Chifley Drive, Preston, VIC 3072

0800 220 120 windsor.yang@ncipackaging.com 80 Mt Wellington Hwy Panmure Auckland

**NEW ZEALAND** 

# **PRODUCT SPECIFICATION**

## 305 Lids for 276 Diameter Pails





LID SPECS		305 Natseal	305 Polyseal (DG)	
	Diameter (mm)	302.6	302.6	
	Height (mm)	13.0	13.0	
	Locking Ring	305	305	
Packing Qty				
Carton	No. per Carton	40	40	
	No. of Cartons	48	48	
	No. per Pallet	1,920	1,920	
Height Tolerance		±1.5mm		
Options		56mm screw nozzle, 63mm UniGrip, 57mm REL or 57mm DIN		
Pails		To suit all 276 diameter pails		
Print Area		Request artwork template from Account Manager		



#### **LID COATINGS**

Outside	Plain	(POS)
	White	(WOS)
	Varnish	(VOS)
Inside	Plain	(PIS)
	Lacquer	(LIS)

Issue Date: 23 April 2021

www.ncipackaging.com

Sales & Enquiries:

AUSTRALIA 1800 289 624 metal.enquiries@ncipackaing.com 90-92 Chifley Drive, Preston, VIC 3072

NEW ZEALAND 0800 220 120 windsor.yang@ncipackaging.com 80 Mt Wellington Hwy Panmure Auckland

# NCI Packaging PRODUCT SPECIFICATION

## **Appendix**

## **COATINGS AND USES**

Tinplate is steel sheet electroplated with tin to provide enhanced appearance and protection again rust. Coatings can be added to tinplate to enhance appearance and performance. Coatings and their typical use's\* are listed below.

Outside Plain (POS)

Use in dry environments where the risk of oxidation is low

White (WOS)

Additional protection again oxidization of the container due to moisture Also used on most printed cans as the white base coating under colour print

Varnish (VOS)

Clear finish for extra protection again oxidization of the container due to moisture

Inside Plain (PIS)

Typical uses:

Solvent based products

Oil paints Edible oils

Not suitable for: Water based products

Olive oil

Lacquer (LIS)

Typical uses:

Water based products Water based paints

Olive oil

www.ncipackaging.com

Sales & Enquiries:

AUSTRALIA 1800 289 624

NEW ZEALAND **0800 220 120** 

metal.enquiries@ncipackaing.com 90-92 Chifley Drive, Preston, VIC 3072

<sup>\*</sup> Uses above are suggestions only, customers are responsible for testing to ensure compatibility of containers with their packed product.